PATENT

BEST AVAILABLE COPY

IN THE CLAIMS.

The claims are to be amended or treated as set forth below. A complete listing of claims follows.

(presently amended) A safety cage for a ladder Comprising a series of safety cage sections spaced in the length of the ladder and cooperating with the ladder to provide a protected "U";

and wherein each section is vertically split so as to provide a vertical split of the safety cage spaced centrally outwardly from the ladder, with one cage component on one side of said vertical split and a second cage component on the opposite side of said vertical split, each cage component including a releasable mechanical securement with the other respective cage component at said vertical split to secure said components to one another at said vertical split, and each component including a releasable mechanical securement at a free edge of the component for attachment to a ladder.

- (original) A safety cage for a ladder as claimed in claim 1 wherein each cage component is supported by a rung of said ladder.
- (presently amended) A safety cage for a ladder Comprising a series of safety cage sections spaced in the length of the ladder and cooperating with the ladder to provide a protected "U";

and wherein each section is vertically split with one cage component on one side of said vertical split and a second cage component on the opposite side of said vertical split, each cage component including a releasable mechanical securement with the

Becker, Allan James SN 10,787,117 #852243.02

BEST AVAILARLE COPY

PATENT

other respective cage component at said vertical split to secure said components to one another at said vertical split at a point outwardly from the ladder, and

each component including a releasable mechanical securement
at a free edge of the component for attachment to a ladder;

A safety cage as claimed-in claim 2

wherein each cage component at said free edge includes a hook for initial placement over a ladder rung for temporary hanging of said components.

- 4. (original) A safety cage as claimed in claim 3 wherein said cage components are of the same shape and interchangeable.
- 5. (original) A safety cage as claimed in claim 4 wherein each component at said free edge includes two hook connectors facing downwardly and one hook connector facing upwardly.
- 6. (original) A safety cage as claimed in claim 5 wherein each hook connector includes a vertically extending "U" shaped channel sized to straddle a vertical support of said ladder.
- 7. (original) A safety cage as claimed in claim 6 wherein each hook connector includes a captured mechanical fastener for effecting securement of said connector to said ladder.
- 8. (original) A safety cage as claimed in claim 1 in combination with a ladder, said ladder comprising two upright members connected by a series of ladder rungs, each upright

Becker, Allan James SN 10,787,117 #852243.02

BEST AVAILABLE COPY

PATENT

member comprising a "U" shaped cross section facing outwardly with said rungs intersecting with a base of each "U" shaped cross section.

- (original) A safety cage in combination with a ladder as claimed in claim 8 wherein each ladder upright member has a series of holes in said base of said "U" shaped section with said series of holes being spaced in the length of said ladder.
- (original) A safety cage in combination with a ladder 10. as claimed in claim 9 wherein each ladder upright member has inwardly extending flanges either side of said "U" shaped cross section forming a restricted connecting structure in each ladder upright member.